

7Kw 32A Home Electric Car AC Type2 Portable EV Charging Stations For Electric Vehicles

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 5
- Price:

Our Product Introduction


- Packaging Details:
- Delivery Time:
- Payment Terms: T/1
- Supply Ability:

	China
	MINKO
	CE(ICR lab), UKCA, ROHS, ISO, REACH
	VPC-62-32AC
y:	5 pieces
	negotiation
	L210xW85xH52 (mm)
	8 -10 working days
	T/T, Western Union, MoneyGram,Paypal,Skrill,Transferwise
	1000000 pieces per month



Product Specification

Highlight:	7kw portable ev car charger,
Electric Cable:	IP65 Circuit Breaker
• Start Method:	Plug And Play
Operating Temperature:	-35°C To 50°C
 Input Power: 	250V Max
Rated Power:	7kW
Rated Current:	32A
 Rated Voltage: 	AC 200-250V
Charging Plug:	IEC 62196 Type 2





More Images



7Kw 32A Home Electric Car AC Type2 Portable EV Charging Stations For Electric Vehicles

Detailed specification:

Portable EV Charger, with power ratings of 3.5KW, 7 kW, is suitable for different types of vehicles. Adjustable current, suitable for various scenarios.

The Voltage and Current are stable during charging, which can protect the battery and delay using time.

We can use normally in ultra-high temperature environment up to 50°C.

It can also be used normally in the -35°C.

Charging plug	IEC 62196 Type 2		
Model No.	VPC-62-32AC		
Rated voltage	AC 200-250V		
Rated current	32A		
Rated power	7kW		
Certificates	CE(ICR lab), UKCA, ROHS,ISO, REACH		
Protection rank	IP54 cable; IP65 circuit breaker		
electric cable	IP65 circuit breaker		
LCD	2.8" LCD screen		
LED indicator	Blue/Red/Green		
Earth leakage protector	30m AC		
input power	250V Max		
length	5m or customized		
Package Size	L210xW85xH52 (mm)		
1	Plug and Play		
Operating temperature-35°C to 50°C			
electrical protection	Overcurrent protection, residual current protection, grounding protection, surge protection, Overvoltage/undervoltage protection, overvoltage/underfrequency protection, overtemperature protection		
Applied Materials	Housing: Black thermoplastic PC940. Corrosion and wear protection. Cable: 4.5M black with TPU jacket. With CE and TUV mark issued by TUV.		
Feature	 The product complies with the Low Voltage Directive 2014/35/EU, IEC61851-1:2019 P67, weatherproof; leakage protection; impact resistance Charging status and working error are simply displayed by LED indicator light and LCD screen Optional function of current selection button, A8A-32A free switching current 		
Warranty	1 Years for the whole machine		

Advanteages:

Temperature Protection Efficient Charging Short Circult Protection Protection Level IP66 Built in Smart Chip



rotection

4

Efficient Charging Short Circuit Protection

Protection Level IP66 5

Built in Smart Chip

Product details





Customizable plug



Customizable







Simple and easy to operate



EV CHARGING



Easy to carry and charge



Packing list

Packing list





Caution:

Don't submerge the EV charging cable in water.

Don't step on, fold or knot the cable.

Don't drop the EV charging box or place a heavy object on it.

Don't place the charging cable near high temperature object when charging.

Don't operate the EVSE in temperatures beyond its operating range of -25°C to 55°C.

Power-supply side input cable should be at least 3*2.5mm (recommended 3*4mm), with a standard 16A socket. It is suggested that

the power distribution is done by the professionals.

Don't put fingers into the charging connector when the power plug is still connecting to the power.

Don't use this EV charging box when the cable is damaged.

The EV charging box is only for EV charging using.

Don't use this device with other brand's extension cord or adapter.

